






Force Gauge Comparison Chart

REV 0923

	 Series 7 Professional	 Series 5 Advanced	 Series 4 Performance	 Series 3 Basic	 Series 2 Economical
Accuracy (% of full scale)	±0.1%	±0.1%	±0.2%	±0.3%	±0.5%
Sampling rate	14,000 Hz	7,000 Hz	3,000 Hz	2,000 Hz	500 Hz
Max data output rate	500 Hz	500 Hz	50 Hz	50 Hz	×
Resolution	1/5,000	1/5,000	1/2,000	1/1,000	1/1,000
Data outputs	USB, RS-232, Mitutoyo, analog	USB, RS-232, Mitutoyo, analog	USB, RS-232, Mitutoyo, analog	USB	×
ASCII command set for external communication	✓	✓	"?" command only (for continuous or individual data point output)	"?" command only (for continuous or individual data point output)	×
Data capture and storage capabilities	Continuous data capture at up to 14,000 Hz*, with buffer, or individually saved readings, 5,000 readings total	1,000 individually saved readings	50 individually saved readings	×	×
Statistical calculations and output to PC	✓	✓	✓	×	×
Break detection*	✓	×	×	×	×
1st / 2nd peak detection*	✓	×	×	×	×
Programmable footswitch command string	✓	×	×	×	×
Averaging mode	✓*	✓	×	×	×
External trigger mode	✓**	✓	×	×	×
Set points (for pass / fail indication)	Yes, with high / low indicators, markers on analog bar graph, and outputs	Yes, with high / low indicators, markers on analog bar graph, and outputs	Yes, with high / low indicators, markers on analog bar graph, and outputs	Yes with high/low indicators, markers on analog bar graph, no output	×
Password protection, for keys and calibration	✓	✓	×	×	×
Overload outputs, w/ pins for tension and compression	✓	✓	✓	×	×
Units of measurement	7, including coefficient of friction unit and user-defined unit	5	5	3	3
Peaks and analog load bar always shown on display	✓	✓	✓	✓	×
Included items	Carrying case with complete set of attachments, AC adapter, rechargeable battery, and calibration cert with data	Carrying case with complete set of attachments, AC adapter, rechargeable battery, and calibration cert with data	Carrying case with complete set of attachments, AC adapter, rechargeable battery, and calibration cert with data	Same as Series 7/5/4, with certificate of calibration without data	AC adapter, rechargeable battery, certificate of conformance

* With configurable automatic data output, data storage, and zero function upon event completion. Can also stop travel of a motorized test stand.

** Can stop travel of a motorized test stand upon event completion.



Mark-10 Corporation ■ www.mark-10.com ■ info@mark-10.com
Toll-free: 888-MARK-TEN ■ Tel: 631-842-9200 ■ Fax: 631-842-9201



Specifications subject to change without prior notice